

2200 ROLLING

The 2200 Kas-Kel Rolling Windows are built on precision-calibrated rollers for smooth fingertip operation and manufactured to last for years. Maximize natural light filtration indoors with a beautifully designed rolling window.

NFRC Thermal Performance Data*

GLAZING	U-FACTOR	SHGC	VLT	CR	ZONE
Energy Star U4	0.23	0.26	0.46	51	N, NC
Energy Star III	0.28	0.36	0.51	59	NC
Low E w/ Argon	0.27	0.28	0.51	63	N, NC
High Perf. Low E	0.31	0.28	0.51	59	NC
Clear	0	0	0	-	

^{*}contact us to see thermal data with grids.

KAS-KEL WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.









	Features	STANDARD	OPTION
S	High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior	Ø	
MATERIALS	Fusion Welded Sash and Frame		
MATE	Sloped Sill and Interlock Leg		
	Sash is easily removed for cleaning.		
H	DP 35 Rating	Ø	
MAN	DP 40 Rating		②
PERFORMANCE	DP 50 Rating		Ø
8	Full 3" Foam insulating Wrap		Ø
	Energy Star III (recommended)		Ø
و	Energy Star U-4		Ø
GLAZING	Clear insulated glass		Ø
ច	Duralite flexible, warm-edge spacers		
	Tints, Heat Reflection and other options available		Ø
SCREENS	Aluminum Extruded Fiberglass 1/2 screen		
	Aluminum framed fiberglass full screen		Ø
	Extruded Aluminum framed locking 1/2 Screen		Ø
	Aluminum Screening Material		Ø
GRILLS	5/8" Contoured Grill Between the Glass		
	3/4" Contoured SDL with spacer bar		Ø
HARDWARE	Smarter Rolling Windows are built on precision-calibrated rollers for long life and smooth fingertip operation. Sash is easily removed for cleaning.	•	
	Our Cam Locks are made of alloyed cast steel to stand up to frequent use.		
	All windows over 28 inches tall have 2 sash locks for maximum protection frame	•	
	Produced in white or beige to seamlessly match your window frame	Ø	
	Increased leverage assures a weather tight seal when locked		

