

700 Picture Slim frame design allows for maximum viewing area

Expansive views and versatile style.

Available in your choice of glass options and grid patterns. The 700 picture window can be configured to work seamlessly with any of our other series of windows and matching trim styles. Fabricated for todays generation.

NFRC Thermal Performance Data*

| GLAZING | U-VALUE | SHGC | VLT |
|-------------------|---------|------|------|
| DOE – R5 – Triple | 0.21 | 0.22 | 0.38 |
| Low E w/ Argon | 0.26 | 0.28 | 0.51 |
| High Perf. Low E | 0.30 | 0.29 | 0.51 |
| Clear | 0.45 | 0.61 | 0.63 |

*contact us to see thermal data with grids.

KAS-KEL WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.



| | Features | STANDARD | OPTION |
|--------------|--|------------|------------|
| MATERIALS | High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior | O | |
| | Thermal Fusion Welded Frame | | |
| | 3" Cambridge Flat Casing | | \bigcirc |
| | Integral Nail Fin and J-Channel | O | |
| | Primed Applied Solid Pine Extension Jambs 4-9/16, 6-9/16 and Custom | | I |
| CONSTRUCTION | 3" Cambridge Flat Casing | | S |
| | Integral Nail Fin and J-Channel | I | |
| | Primed Solid Pine Applied Extension Jambs 4-9/16", 6-9/16" and Custom | | I |
| PERF. | DP 50 Rating | \bigcirc | |
| GLAZING | Energy Star III | \bigcirc | |
| | Energy Star U-4 | | S |
| | DOE R5 Triple Glass Package | | S |
| | Clear insulated glass | | S |
| | Duralite flexible, warm-edge spacers | \bigcirc | |
| | Impact Resistance, Tints, Heat Reflection and other options available | | I |
| GRILLS | 3/4" Contoured Grill Between the Glass | | I |
| | 3/4" Contoured SDL with spacer bar | | S |

