



220 Series | Double Hung

High thermal efficiency - exceptionally solid design

The standard window with all the superior features.

The 220 new construction series double hung comes with superior features over the ordinary new construction window- including thermal performance that will exceed Energy Star, choice of top and bottom sash ventilation, easy clean feature, peace of mind locking system.

Fabricated for today's generation.

NFRC Thermal Performance Data*

GLAZING	U-VALE	SGGC	VLT	CR	Zone
Energy Star U4	0.25	0.27	0.48	47	N,NNC
Energy Star III	0.29	0.37	0.51	59	NC
Low E w/ Argon	0.28	0.28	0.51	63	NC
High Perf. Low E	0.32	0.28	0.51	58	
Clear	0	0	0	0	

*contact us to see thermal data with grids.

KAS-KEL WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.



Features

	STANDARD	OPTION
MATERIALS	High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior	✓
	Full Fusion Welded Sash and Frame	✓
	Sloped Sill and Interlock Leg	✓
	3-1/4" Frame Depth	✓
PERF.	DP 40 Rating	✓
	DP 50 Rating	✓
	Full 3" Foam insulating Wrap	✓
GLAZING	Energy Star III (recommended)	✓
	Energy Star U-4	✓
	Clear insulated glass	✓
	Duralite flexible, warm-edge spacers	✓
	Tints, Heat Reflection and other options available	✓
SCREENS	Extruded aluminum framed fiberglass full screen	✓
	Extruded aluminum framed locking 1/2 Screen	✓
	Full Flex Screens on painted exterior frames	✓
	Aluminum Screening Material	✓
CONSTRUCTION	Composite Reinforced Meeting Rail	✓
	Bottom and Top Sash Tilt in for easy cleaning	✓
	Double weather stripped Meeting Rail	✓
	Nailing fin with J Channel	✓
	Nail Fin Only	✓
	Egress Sizing Available	✓
	Primed Solid Pine Applied Extension Jamb 4-9/16", 6-9/16" and Custom	✓
Sheet Rock Returns	✓	
HARDWARE	All windows over 23 1/2 inches have 2 sash locks for maximum protection	✓
	Produced in white or beige to seamlessly match your window frame	✓
	Night Latches	✓
	WOCD sash limiters	✓
GRILLS	5/8" Contoured Grill Between the Glass	✓
	3/4" Contoured SDL with spacer bar	✓

