

300 Double Hung *integrated brickmold trim package*

Traditional Look

The 300 Double Hung window utilizes an integrated **brickmold trim** package or a 3 1/2" vinyl trim option, both of which also serve as a J-channel pocket for easy installation. An elegant, classic look and advanced design with high thermal ratings and glazing package options that meet or exceed Energy Star requirements.

| GLAZING | U-VALUE | SHGC | VLT | | |
|------------------|---------|------|------|----|------|
| Energy Star U4 | 0.23 | 0.27 | 0.48 | 51 | N,NC |
| Energy Star III | 0.27 | 0.37 | 0.52 | 51 | NC |
| Low E w/ Argon | 0.27 | 0.28 | 0.52 | 63 | NC |
| High Perf. Low E | 0.31 | 0.28 | 0.52 | 63 | |
| Clear | 0 | 0 | 0 | - | |

*contact us to see thermal data with grids.

KAS-KEL WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.



Features

| | | STANDARD | OPTION |
|--------------|---|----------|--------|
| MATERIALS | High-grade PVC delivers exceptional strength and thermal performance. White or beige Interior | ✓ | |
| | Fusion Welded Sash and Frame | ✓ | |
| | Sloped Sill with Interlocking Leg | ✓ | |
| | 3-5/8" Frame Depth | ✓ | |
| PERF | DP 35 Rating | ✓ | |
| | DP 50 Rating | | ✓ |
| GLAZING | Energy Star III | ✓ | |
| | Energy Star U-4 Glass | | ✓ |
| | Double Strength Glass | | ✓ |
| | Clear insulated glass | | ✓ |
| | Duralite flexible, warm-edge spacers | ✓ | |
| | Tints, Heat Reflection and other options available | | ✓ |
| SCREENS | Aluminum framed fiberglass full screen | ✓ | |
| | Aluminum framed fiberglass half screen | | ✓ |
| | Full Flex Screen on painted products | | ✓ |
| | Aluminum Screening Material | | ✓ |
| HARDWARE | All windows over 23 1/2 inches have 2 sash locks for maximum protection | ✓ | |
| | Night Latches | | ✓ |
| | WOCD sash limiters | | ✓ |
| CONSTRUCTION | Produced in white or beige to seamlessly match your window frame | ✓ | |
| | Brickmold exterior profile | ✓ | |
| | Composite Reinforced Meeting Rail | ✓ | |
| | Nailing fin with J Channel | ✓ | |
| | Double weather stripped Meeting Rail | ✓ | |
| | J Channel Filler | | ✓ |
| | Bottom and Top Sash Tilt in for easy cleaning | ✓ | |
| | Primed Solid Pine Applied Extension Jambos 4-9/16", 6-9/16" and Custom | | ✓ |
| GRILLS | 3/4" Contoured Grill Between the Glass | | ✓ |
| | 3/4" Contoured SDL with spacer bar | | ✓ |