

The replacement awning

Easy operation and maximum ventilation

window with superior features The unique style and lines will catch your eye as will the performance and sizing features it includes. Stacked side by side or over the top of a primary window will work with great ease, giving you the flexibility

needed when designing your home. Designed for today's generation.

NFRC Thermal Performance Data*

GLAZING	U-VALUE	SHGC	CR	VLT
DOE-R5	0.19	0.19	77	0.33
Energy Star U-4	0.23	0.23	52	0.41
Energy Star III	0.26	0.32	65	0.44
Low E Argon	0.26	0.24	65	0.44
Low E HP	0.29	0.24	61	0.44
Clear	0.41	0.53	46	0.54

^{*}contact us to see thermal data with grids.

		Features	STANDARD	OPTION
	MATERIALS	High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior	•	
		Fusion Welded Sash and Frame	②	
		Exterior Beveled Sash	Ø	
		Sash Snubbers	Ø	
		Double weather stripped Sash		②
	Ë.	DP 50 Rating	Ø	
	PERF.	Full 3" Foam insulating Wrap		Ø
	GLAZING	Energy Star III (recommended)		Ø
		Energy Star U-4		Ø
		DOE R5 Triple Glass Package		Ø
		Clear insulated glass		⊘
		Duralite flexible, warm-edge spacers	Ø	
		Tints, Heat Reflection, Impact Resistance and other options available		⊘
	HARDWARE	Produced in white or beige to seamlessly match your window frame		
		Single Lever Multi-Point Locking System	②	
		Folding Hardware		
	SNE	Extruded aluminum framed fiberglass full screen		
	SCREENS	Aluminum Screening Material		⊘
	GRILLS	3/4" Contoured Grill Between the Glass		
		3/4" Contoured SDL with spacer bar		Ø
		2" Contoured SDL with spacer bar for simulated Double Hung look		Ø

KAS-KEL WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.









