

The 300C Picture window utilizes a New England Style 3 1/2" Cambridge Flat Casing which integrates a built -in J-channel pocket for siding and nail-fin for installation. (filler available). An elegant, classic look and advanced design with high thermal ratings and glazing package options that meet or exceed Energy Star requirements. Factory applied off the edge design ensures maximum weather protection.

## NFRC Thermal Performance Data\*

GLAZING	U-VALUE	SHGC	VLT
Energy Star U4	0.22	0.28	0.50
Low E w/ Argon	0.25	0.30	0.55
Energy Star III	0.26	0.39	0.55
High Perf. Low E	0.29	0.30	0.55
Clear	0.45	0.65	0.68

<sup>\*</sup>contact us to see thermal data with grids.

**KAS-KEL WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN** THE INDUSTRY.









	Features	STANDARD	OPTION
MATERIALS	High-grade PVC delivers exceptional strength and thermal performance. White or beige Interior	•	
	Fusion Welded Sash and Frame	<b>Ø</b>	
	3 ¼" Frame Depth	<b>Ø</b>	
PERF	DP 35 Rating	•	
GLAZING	Energy Star III	<b>②</b>	
	Energy Star U-4		<b>Ø</b>
	Clear insulated glass		
	Duralite flexible, warm-edge spacers		
	Tints, Tempered and Double Strength and other options available		<b>Ø</b>
GRILLS	3/4" Contoured Grill Between the Glass		$\bigcirc$
	3/4" Contoured SDL with spacer bar		<b>Ø</b>
CONSTRUCTION	Integral Nail Fin		
	Integral Nail Fin and J-Channel		
	Available without J-Channel		<b>Ø</b>
	4 9/16" , 6 9/16", and custom Pre-Primed Extension Jamb		<b>Ø</b>
	3 ½" Cambridge Flat Casing		

