

300 Double Hung *integrated brickmold trim package*

For a clean look and easy installation

The 300 Double Hung window utilizes an *integrated brickmold trim package* or a 3 1/2" vinyl trim option, both of which also serve as a J-channel pocket for easy installation. An elegant, classic look and advanced design with high thermal ratings and glazing package options that meet or exceed Energy Star requirements.

NFRC THERMAL PERFORMANCE DATA*

	U-Factor	SHGC	CT	U-Factor	U-Factor
Clear-Air-Clear	0.45	0.62	0.63	46	
Energy Star U4	0.23	0.27	0.48		
Low E w/ Argon	0.27	0.28	0.52	63	NC
Energy Star III	0.27	0.37	0.52	51	N,NC
High Perf. Low E	0.31	0.28	0.52	63	NC

*contact us to see thermal data with grids.

**SMARTER NEW CONSTRUCTION WINDOWS WILL OFFER YOU
A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF
THE BEST WARRANTIES IN THE INDUSTRY.**



Features

		STANDARD	OPTION
MATERIALS	High-grade PVC delivers exceptional strength and thermal performance. White or beige Interior	✓	
	Fusion Welded Sash and Frame	✓	
	Sloped Sill with Interlocking Leg	✓	
	3-5/8" Frame Depth	✓	
PERFORMANCE	DP 35 Rating	✓	
	DP 50 Rating		✓
	Full 3" Foam insulating Wrap <i>(install required replacements AMA)</i>		✓
GLAZING	Energy Star III	✓	
	Energy Star U-4 Glass		✓
	Double Strength Glass		✓
	Clear insulated glass (3/4")		✓
	Duralite flexible, warm-edge spacers		
	Tints, Heat Reflection and other options available		✓
SCREENS	Aluminum framed fiberglass full screen (new construction windows)	✓	
	Aluminum framed fiberglass half screen		✓
	Full Flex Screen on painted products		✓
	Aluminum Screening Material		✓
HARDWARE	All windows over 23 1/2 inches have 2 sash locks for maximum protection	✓	
	Night Latches (300)	✓	
	WOCD sash limiters (300)		✓
	Produced in white or beige to seamlessly match your window frame (300)	✓	
CONSTRUCTION	Brickmold exterior profile	✓	
	Composite Reinforced Meeting Rail	✓	
	Nailing fin with J Channel	✓	
	Double weather stripped Meeting Rail	✓	
	J Channel Filler		✓
	Bottom and Top Sash Tilt in for easy cleaning	✓	
	Primed Solid Pine Applied Extension Jambos 4-9/16", 6-9/16" and Custom		✓
GRILLS	3/4" Contoured Grill Between the Glass		✓
	3/4" Contoured SDL with spacer bar		✓